


QUARTZ 9000 5W-40



Synthetic technology multigrade oil for Gasoline and Diesel engines

USES

- TOTAL QUARTZ 9000 5W-40 has been developed to cover the most stringent requirements of **both recent gasoline and diesel engines** (since MY 2000).
- TOTAL QUARTZ 9000 5W-40 is particularly suited to **turbocharged, multi-valve and direct injection engines**.
- TOTAL QUARTZ 9000 5W-40 can be used in the **most difficult operating conditions** (motorways, dense city traffic...), **whatever the season**.
- TOTAL QUARTZ 9000 5W-40 is perfectly **adapted to all vehicles equipped with catalysts** and using unleaded fuel or liquefied petroleum gas.

PERFORMANCES

Specifications	ACEA 2007 API	A3/B4 SM/CF
OEMs	NORM PSA PEUGEOT CITROEN B71 2296 Gasoline and Diesel VOLKSWAGEN 502.00/505.00 BMW Longlife oil 01 MB 229.3 PORSCHE	



CUSTOMER BENEFITS

Extended drain interval	<ul style="list-style-type: none">• Exceptional oxidation resistance.
All operating conditions	<ul style="list-style-type: none">• Easy cold starts and fuel economies due to its extreme fluidity; at low temperature; and a very resistant oil film even at high temperature
Mechanical parts protection	<ul style="list-style-type: none">• Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength
Mechanical parts cleaning	<ul style="list-style-type: none">• Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives

CHARACTERISTICS

TOTAL QUARTZ 9000 5W-40	Units	SAE Grade 5W-40
Volumetric mass at 15°C	kg/m ³	854.3
Viscosity at 40°C	mm ² /s	82.19
Viscosity at 100°C	mm ² /s	13.60
Viscosity index	-	169
Flash point Cleveland	°C	228
Pour point	°C	-39

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'île
92029 Nanterre Cedex
1/1

QUARTZ 9000 5W-40
Sheet updated : 01/09
Sticker reference: MPC 01/09



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant